

Product Design

Foam-LOK™ CC is a closed-cell spray applied foam, which was developed using Environment Canada's approved next generation blowing agent. When installed following application guidelines the spray foam insulation adheres tenaciously to framing members and substrates. Foam-LOK™ CC closed-cell spray foam provides superior energy economy and durability while significantly reducing unmanaged moisture and air infiltration.

Product Use

As a component of a "systems approach" to proper building envelope construction, Foam-LOK™ CC closed-cell spray foam provides exceptional performance in reducing heat transfer, moisture gain and significantly improving racking strength.

Recommended Product Applications

- Walls
- Floors
- Unvented Crawl Spaces
- Concrete Slabs
- Cold Storage
- Unvented Attics
- Vented Attics
- Vented Crawl Spaces
- Ducts
- Freezers
- Ceilings
- Piping
- Foundations
- Tanks
- Coolers

Recommended Processing Parameters

Processing Designation:	Regular
Ambient Temperature:	50-120°F

Optimum hose pressure and temperature may vary as a function of the type of equipment, ambient and substrate conditions, and the specific application. It is the responsibility of the applicator to properly interpret equipment technical literature, particularly information that relates acceptable combinations of gun chamber size, proportioner output, and material pressures.

Processing Designation:	Foam-LOK CC
Equipment Dynamic Pressure:	1,000 - 1,400 psi
Preheat Temperature	125 - 135 ° F (52 - 57° C)
Hose Heat Temperature	125 - 135 ° F (52 - 57° C)
Drum Temperature: Storage	65 - 85° F (18 - 30° C)

Material shelf life: **6 months** when stored within recommended temperature range.

2:1 transfer pumps are recommended for material transfer from container to the proportioner.

CAUTION: Extreme care must be taken when removing and reinstalling drum transfer pumps so as NOT to reverse the "A" and "B" components.

Do not configure equipment to circulate Foam-LOK CC from proportioner back into drum. Do not recirculate or mix other suppliers' "A" or "B" component into Foam-LOK containers.

Physical Properties

Properties	Test Method/ Requirements	Value
Aged "R" Value:	ASTM C-518	6.3 per inch
Compressive Strength:	ASTM D-1621	25-30 psi
Core Density:	ASTM D-1622	2.0-2.3 lbs./ft3
Closed Cell Content:	ASTM D-2856	>90%
Tensile Strength:	ASTM D-1623 15 minimum	40-48 psi
Water Vapor Transmission @ 74°F, perm inch	ASTM E-96 2.5 max	1.98 perms @ 1"
Dimensional Stability: 28 days at 160°F, 100%RH	ASTM D-2126 15% max by volume change	4%
Sound Transmission Co-Efficient	ASTM E-90-85/ E413 Sound Transmission Loss in dB	38

Credentials/Certifications

- CCMC 13414-L
- CAN/ULC S705.1

Foam-LOK CC is a **Class I** formulation, as Tested per ASTM E84, and possess the flammability characteristics shown:

ASTM Method E84	Class I	Class II	Class III
Flame Spread	≤25 Foam-LOK CC ≤10	≤75	Non Rated
Smoke Development	≤450	≤450	Non Rated

Room Corner Fire Testing

NFPA 286	
Location	SPF Thickness
Wall Cavities	Up to 12in (305mm)
Ceiling Cavities	Up to 12in (305mm)

Diversified	
Location	SPF Thickness
Wall Cavities	Up to 7in (178mm)
Ceiling Cavities in Attics	Up to 15in (385mm)

Thermal Barrier

The National, Provincial and Local building codes require that SPF be separated from the interior of a building by an approved fifteen (15) minute thermal barrier, such as 1/2" gypsum wall board or equivalent, installed per manufacturer's instructions and corresponding code requirements. There are exceptions to the thermal barrier requirement: (1) Code authorities may approve coverings based on fire tests specific to the SPF application. For example, covering systems that successfully pass large scale tests may be approved by code authorities in lieu of a thermal barrier; (2) SPF protected by 1" thick masonry does not need a thermal barrier. Certain materials that offer protection from ignition, called "ignition barriers," may not be considered as thermal barrier alternatives unless they comply with NFPA 286 or other full-scale burn tests. Applicators should request test data and code body approvals or other written indications of acceptability under the code to be sure that the product selected offers code-compliant protection. Applicators should ensure the safety of the jobsite and construction personnel by posting appropriate signs warning that all "hot work" such as welding, soldering, and cutting with torches should take place no less than 35 feet from any exposed foam. If "hot work" must be performed all spray polyurethane foam should be covered with an appropriate fire or welder's blanket, and a fire watch should be provided.

Air Barrier

Foam-LOK CC qualifies as an air barrier as defined by the National Research Council of Canada (class III).

Handling and Safety

Respiratory protection is **MANDATORY!** Contact Lapolla Industries for a copy of the Model Respiratory Protection Program developed by API or visit their website at www.polyurethane.org. Persons with known respiratory allergies should avoid exposure to the "A" component. The "A" component contains reactive isocyanate groups while the "B" component contains amine and/or catalysts with blowing agents. Both materials must be handled and used with adequate ventilation. The vapors must not exceed the TLV (0.02 parts per million) for isocyanates. Avoid breathing vapors. Wear a NIOSH approved respirator. If inhalation of vapors occur, remove victim from contaminated area and administer oxygen if breathing is difficult.

Call a physician immediately. Avoid contact with skin, eyes, and clothing. Open containers carefully, allowing any pressure to be relieved slowly and safely. Wear chemical safety goggles and rubber gloves when handling or working with these materials. In case of eye contact, immediately flush with large amounts of water for at least fifteen minutes. Consult a physician immediately. In case of skin contact, wash area with soap and water. Wash clothes before reuse.

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact Lapolla Industries, Inc. to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Lapolla Industries, Inc.'s quality control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of product. **NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY LAPOLLA INDUSTRIES, INC., EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

In Case of Spills or Leaks

Steps To Be Taken-

- Utilize appropriate personal protective equipment (PPE.)
- Contain and cover spilled material with a loose, absorbent material such as oil-dry, vermiculite, sawdust or Fuller's earth.
- Shovel absorbent waste material into proper waste containers
- Wash the contaminated areas thoroughly with hot, soapy water.
- Ventilate area to remove vapors.
- Report sizeable spills to proper environmental agencies.

In Case of Fire

Extinguishing Media-Dry chemical extinguishers such as mono ammonium phosphate, potassium sulfate, and potassium chloride. Additionally, carbon dioxide, high expansion (proteinic) chemical foam, or water spray for large fires.

DISCLAIMER

The data presented herein is not intended for use by nonprofessional applicators, or those persons who do not purchase or utilize this product in the normal course of their business. The potential user must perform any pertinent tests in order to determine the product's performance and suitability in the intended application, since final determination of fitness of the product for any particular use is the responsibility of the buyer.

All guarantees and warranties as to products supplied by Lapolla Industries shall have only those guarantees and warranties expressed in writing by the manufacturer. The buyer's sole remedy as to any material claims will be against the applicator of the product. The aforementioned data on this product is to be used as a guide and is subject to change without notice. The information herein is believed to be reliable, but unknown risks may be present. **NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING PATENT WARRANTIES OR WARRANTIES OF MERCHANTABILITY OR FITNESS FOR USE, ARE MADE BY LAPOLLA WITH RESPECT TO OUR PRODUCTS OR INFORMATION SET FORTH HEREIN.**